

Specifications

| Models | GS-1530 | | GS-1532 | | GS-1930 | | GS-1932 | |
|--------------------------------------|---------|-------------|---------|-------------|---------|-------------|---------|-------------|
| Measurements | Metric | US | Metric | US | Metric | US | Metric | US |
| Working height maximum* | 6.40 m | 20 ft 11 in | 6.40 m | 20 ft 11 in | 7.60 m | 24 ft 11 in | 7.60 m | 24 ft 11 in |
| Platform height maximum w/load sense | 4.40 m | 14 ft 5 in | 4.40 m | 14 ft 5 in | 5.60 m | 18 ft 5 in | 5.60 m | 18 ft 5 in |
| Platform height - stowed | 0.97 m | 3 ft 2.2 in | 0.97 m | 3 ft 2.2 in | 1.00 m | 3 ft 3.5 in | 1.00 m | 3 ft 3.5 in |
| Platform length - outside | 1.63 m | 5 ft 4 in | 1.63 m | 5 ft 4 in | 1.63 m | 5 ft 4 in | 1.63 m | 5 ft 4 in |
| extended | 2.54 m | 8 ft 4 in | 2.54 m | 8 ft 4 in | 2.54 m | 8 ft 4 in | 2.54 m | 8 ft 4 in |
| Slide-out platform extension deck | 0.91 m | 3 ft | 0.91 m | 3 ft | 0.91 m | 3 ft | 0.91 m | 3 ft |
| Platform width - outside | 0.74 m | 2 ft 5 in | 0.74 m | 2 ft 5 in | 0.74 m | 2 ft 5 in | 0.74 m | 2 ft 5 in |
| Guardrail height | 1.10 m | 3 ft 7 in | 1.10 m | 3 ft 7 in | 1.10 m | 3 ft 7 in | 1.10 m | 3 ft 7 in |
| Toeboard height | 0.15 m | 6 in | 0.15 m | 6 in | 0.15 m | 6 in | 0.15 m | 6 in |
| Height - stowed: bolted rails | 2.03 m | 6 ft 9 in | 2.03 m | 6 ft 9 in | 2.11 m | 6 ft 11 in | 2.11 m | 6 ft 11 in |
| rails folded | 1.73 m | 5 ft 8 in | 1.73 m | 5 ft 8 in | 1.75 m | 5 ft 9 in | 1.75 m | 5 ft 9 in |
| Length - stowed | 1.83 m | 6 ft | 1.83 m | 6 ft | 1.83 m | 6 ft | 1.83 m | 6 ft |
| Length - stowed extended | 2.74 m | 9 ft | 2.74 m | 9 ft | 2.74 m | 9 ft | 2.74 m | 9 ft |
| Width | 0.76 m | 2 ft 6 in | 0.813 m | 2 ft 8 in | 0.76 m | 2 ft 6 in | 0.813 m | 2 ft 8 in |
| Wheelbase | 1.32 m | 4 ft 4 in | 1.32 m | 4 ft 4 in | 1.32 m | 4 ft 4 in | 1.32 m | 4 ft 4 in |
| Ground clearance - center | 6 cm | 2.4 in | 6 cm | 2.4 in | 6 cm | 2.4 in | 6 cm | 2.4 in |
| - with pothole guards deployed | 2 cm | 0.75 in | 2 cm | 0.75 in | 2 cm | 0.75 in | 2 cm | 0.75 in |

Productivity

| Max platform occupancy (in/out) ¹ | 2/- | | 2/1 | | 2/- | | 2/1 | |
|--|-------------------------|-------------|-------------------------|-------------|-------------------------|-------------|-------------------------|-------------|
| Lift capacity | 272 kg | 600 lbs | 272 kg | 600 lbs | 227 kg | 500 lbs | 227 kg | 500 lbs |
| Drive speed - stowed | 4.0 km/h | 2.5 mph | 4.0 km/h | 2.5 mph | 4.0 km/h | 2.5 mph | 4.0 km/h | 2.5 mph |
| Drive speed - raised | 0.8 km/h | 0.5 mph | 0.8 km/h | 0.5 mph | 0.8 km/h | 0.5 mph | 0.8 km/h | 0.5 mph |
| Gradeability - stowed** | 30% | 30% | 30% | 30% | 25% | 25% | 25% | 25% |
| Turning radius - inside | zero | zero | zero | zero | zero | zero | zero | zero |
| Turning radius - outside | 1.55 m | 5 ft 1 in | 1.55 m | 5 ft 1 in | 1.55 m | 5 ft 1 in | 1.55 m | 5 ft 1 in |
| Raise / lower speed | 16 / 29 sec | 16 / 29 sec | 16 / 29 sec | 16 / 29 sec | 16 / 29 sec | 16 / 29 sec | 16 / 29 sec | 16 / 29 sec |
| Controls | proportional | | proportional | | proportional | | proportional | |
| Drive | dual front wheel | | dual front wheel | | dual front wheel | | dual front wheel | |
| Multiple disc brakes | dual rear wheel | | dual rear wheel | | dual rear wheel | | dual rear wheel | |
| Tyres - solid non-marking | 30x11x20 cm 12x4.5x8 in | | 30x11x20 cm 12x4.5x8 in | | 30x11x20 cm 12x4.5x8 in | | 30x11x20 cm 12x4.5x8 in | |

Power

| Power source | 24 V (four 6 V 225 Ah batteries) | | | | | | | |
|---------------------------|----------------------------------|----------|--------|----------|--------|----------|--------|----------|
| Hydraulic system capacity | 14.2 L | 3.75 gal | 14.2 L | 3.75 gal | 14.2 L | 3.75 gal | 14.2 L | 3.75 gal |

Sound & Vibration Levels


| | | | | | | | | |
|---|-----------------------|---------------------------|-----------------------|---------------------------|-----------------------|---------------------------|-----------------------|---------------------------|
| Sound pressure level (ground workstation) | <70 dBA | <70 dBA | <70 dBA | <70 dBA | <70 dBA | <70 dBA | <70 dBA | <70 dBA |
| Sound pressure level (platform workstation) | <70 dBA | <70 dBA | <70 dBA | <70 dBA | <70 dBA | <70 dBA | <70 dBA | <70 dBA |
| Vibration | <2.5 m/s ² | <8 ft 2 in/s ² | <2.5 m/s ² | <8 ft 2 in/s ² | <2.5 m/s ² | <8 ft 2 in/s ² | <2.5 m/s ² | <8 ft 2 in/s ² |

Weight***

| | | | | | | | | |
|--|----------|-----------|----------|-----------|----------|-----------|----------|-----------|
| | 1,233 kg | 2,718 lbs | 1,269 kg | 2,797 lbs | 1,498 kg | 3,302 lbs | 1,503 kg | 3,313 lbs |
|--|----------|-----------|----------|-----------|----------|-----------|----------|-----------|

Standards Compliance

EU Directives: 2006/42/EC - Machinery (harmonized standard EN280:2013); 2004/108/EC (EMC); 2006/95/EC (LVD)



¹ Indoor use only for the 30' Series
^{*} The metric equivalent of working height adds 2 m to platform height.
^{**} Gradeability applies to driving on slopes, see Operator's Manual for details regarding slope ratings.
^{***} Weight will vary depending on options and/or country standards.

Features

| Standard Features | Easily Configured To Meet Your Needs | Options & Accessories |
|---|---|---|
| <p>Measurements</p> <p>GS-1530 & GS-1532</p> <ul style="list-style-type: none"> • 6.40 m (20 ft 11 in) working height • Up to 272 kg (600 lbs) lift capacity <p>GS-1930 & GS-1932</p> <ul style="list-style-type: none"> • 7.60 m (24 ft 11 in) working height • Up to 227 kg (500 lbs) lift capacity <p>Productivity</p> <ul style="list-style-type: none"> • Bolted rails with half-height swing gate • Smart Link™ control system (joystick, 2 lift speeds & 2 selectable proportional drive speeds, user-friendly diagnostics) • Rear recessed charger receptacle • Platform control with battery charge indicator • On-board diagnostic system • AC power to platform • Lanyard attachment points • Manual platform lowering valve • Emergency stop at both platform and ground controls • Rear wheel multiple disc brakes • Front wheel hydraulic dynamic braking • Manual brake release • Swing-out component trays • Pothole guards • Tilt level sensor with audible alarm • Descent alarm • Flashing beacons • Electronic horn • Hour meter • Certified load sensor • Telematics-Ready Connector <p>Power</p> <ul style="list-style-type: none"> • 24 V DC battery pack • Universal 20 amp smart charger | <p>Platform</p> <ul style="list-style-type: none"> • 1.63 x 0.74 m (5 ft 4 in x 2 ft 5 in) steel platform • 0.91 m (3 ft) slide-out extension deck <p>Power</p> <ul style="list-style-type: none"> • 24 V DC (four 24 V 225 Ah batteries) <p>Drive</p> <ul style="list-style-type: none"> • Dual front wheel drive <p>Tyres</p> <ul style="list-style-type: none"> • Solid non-marking | <p>Productivity Options</p> <ul style="list-style-type: none"> • Air line to platform • Power to platform (incl. plug, socket and ground fault interrupt leakage on request) • Biodegradable hydraulic oil⁽²⁾ • Track & Trace⁽¹⁾ (GPS unit providing machine location & operating information) • Motion alarm package • Automotive horn <p>Power Options</p> <ul style="list-style-type: none"> • Maintenance-free batteries • Low-temperature cut-out module⁽³⁾ |



⁽¹⁾ Includes a first 2 years subscription
⁽²⁾ Available on selected models only. See your Genie representative for further information.
⁽³⁾ For outdoor models only



07/15 Part No. B109377UK

United Kingdom

The Maltings, Wharf Road, Grantham NG31 6BH, T: +44 800 988 3739 (toll free), Fax +44 (0)1476 584334, Email AWP-InfoEurope@terex.com
 Visit www.genielift.co.uk/locations to view our global locations list.

Worldwide Manufacturing And Distribution

Australia · Brazil · Caribbean · Central America · China · France · Germany · Italy · Japan · Korea · Mexico · Russia · Southeast Asia · Spain · Sweden · United Arab Emirates · United Kingdom · United States

Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Genie is a registered trademark of Terex South Dakota, Inc. © 2015 Terex Corporation.

